



Nonfood Compounds
Program Listed 3H / H1
Registration No. 170757

Vaseline Oil 15

art. 908

Description: Vaseline Oil 15 is a pharmaceutical white oil for lubricating machines in the food, feed, and pharmaceutical industries as well as the printing, paper, and textile industries.

Area of application: Vaseline Oil 15 is an excellent release agent, binding agent, and lubricant for direct contact with food on grills, ovens, baking tins, benches, cutting boards, knives, handcars, dough rollers, or other hard surfaces in contact with meat, poultry, and dough products, raw and dried fruit and vegetables, and capsules and tablets to prevent food from adhering during processing. The quantities authorized for direct contact can be found in the relevant legal provisions. It is also suitable for lubrication points with low loads on manufacturing, filling, and packaging machines, precision mechanical equipment, chains, slat conveyors, and pneumatic maintenance units, etc. and also wherever high chemical purity is demanded of the lubricant and a product based on pharmaceutical white oil is required.

Product properties

- NSF H1 & 3H registered
FDA regulation 21 CFR 178.3570
Kosher-certified, Halal-certified,
odorless and tasteless
- Meets the purity requirements for
the following specifications:
Deutsches Arzneibuch (DAB),
British Pharmacopoeia (BP),
European Pharmacopoeia (PhEur),
United States Pharmacopoeia (USP)
- Very high degree of refinement
- Very high stability in contact with
mineral oil resistant seals
- Designed for various lubrication points
where a watery appearance is required
for the lubricant

Benefits

- A high level of safety is ensured with regard to contamination of the manufactured goods. Facilitates compliance with the provisions of the Swiss Ordinance on Foodstuffs and Utility Articles (LGV). Supports due diligence and compliance with quality management according to DIN EN ISO 9001.
- Supports operational safety according to the high requirements placed on a pharmaceutical product.
- No impairment of odor and taste in the environment.
- No impairment of commonly used elastomers (e.g., seals).
- The machine elements are lubricated while maintaining a high degree of cleanliness.

Application: The food-relevant requirements according to FDA regulation 21 CFR 178.3570, NSF H1 are only met with unmixed Vaseline Oil 15.
Meaning of H1: Lubricants authorized for unintended contact with food, feed, and pharmaceutical products.
Meaning of 3H: Mold release lubricants which have intended or technically unavoidable contact with food and feed during the manufacturing process.

Physical-chemical data: See reverse

Vaseline Oil 15

art. 908

Physical-chemical data:

Art. no.	Viscosity (mm ² /s)			ISO VG class	Viscosity index VI	Density at 20°C (g/ml)	Pour point (°C)	Flash point (°C)
	20°C	40°C	100°C					
908	33	15	3.5	15	110	0.844	-9	180

Safety and environmental aspects:

ADR/RID:

Precautionary measure:

Water hazard class:

LVA / EU waste code:

CH waste code:

Classification and labeling:

Not classified as hazardous by transport regulations

Do not allow to get into groundwater, surface water, or waste water. Harmful to water-borne organisms.

Slightly hazardous to water (WGK 1, German water hazard class 1)

13 02 05

Identical to the EU waste code (as per VeVA from January 1, 2006)

See Safety Data Sheet


Container sizes:

Drum: 208 L

Canister: 5 L • 10 kg

The information provided in this data sheet is based on the properties and uses we are aware of. Blaser Swisslube AG is not liable for injury resulting from improper use of the products. As a general rule, no legal obligation can be derived from this information. 30.524 en (0126)