

Blasoprotect MV 25

Art. 125-02

Description: Blasoprotect MV 25 is an anti-corrosion oil containing solvents. It forms a thin transparent film that does not dry out completely.

Applications: – Suitable for all machinery stored under cover, motor vehicles and bare metal parts. Does not attack rubber, paint, chromium or aluminium. The anti-corrosion film does not have to be removed before putting machinery into operation.

Product characteristics

- Protects against corrosive substances
- Good bonding
- Transparent thin protective film
- Does not attack elastomeric materials



Benefits



- Good protection and longer life of treated machinery and components
- Protects efficiently against dirt and humidity
- Clean and economical
- Wide application range

Product related data:

Type of film:	<i>oily</i>
Film thickness by dip-coating:	<i>10 µm</i>
Drying time at room temperature:	<i>1 h</i>
Protection duration in months:	<i>Indoor storage: 12, under cover: 6</i>
Condensation water test to DIN 50'017:	<i>3 cycles without corrosion</i>
Amount required per m2 (dip-coating):	<i>Approx. 12 grams</i>
Application methods:	<i>Dip-coating, brushing</i>
Film removal method:	<i>Neutral cleaner, alkaline cleaner, solvent</i>

Physical- chemical data:

Viscosity:	<i>6 mm²/s (40°C)</i>
Density:	<i>0.85 g/cm³</i>
Flashpoint:	<i>53°C</i>

Safety and environmental aspects:

ADR/RID:	UN 1993
Precautionary measure:	Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.
Water hazard class:	Strongly dangerous to water (WGK 3)
LVA/EU waste codes:	20 01 13 and 12 01 07
CH waste code:	Identical to EU waste code (as per VeVA waste regulations of 01.01.06)
Classification and labelling:	Stated in the safety data sheet



Container sizes: Drum: 60 l • 208 l

Can: 5 l • 25 l

These specifications are subject to frequent change. Alterations are therefore reserved. The data given on this sheet are based on properties and application possibilities as known to us. No general legal liability can be derived from these data. Blaser Swisslube AG cannot be held liable for any damages resulting from the improper use of its products.

39.538 E (0223)