

Blasoprotect MV 27

Art. 127-02

Description: **Waxy anticorrosion fluid containing solvents, with wide applications. Dries to form a transparent protective film.**

Applications: – For tools and forms, jigs and fixtures, bare metal parts, intermediate storage of machinery and vehicles, and wherever temporary protection against corrosion is required.

Product characteristics

- Displaces water
- Forms a dry protective film
- Good penetration

Benefits

- good protection against moisture.
- prevents dust and dirt from sticking (wide applications).
- also protects inaccessible zones.

Product-related data:

Film type:	<i>Waxy</i>
Film thickness by dip method:	<i>1.7 µm</i>
Drying time at room temperature:	<i>1 hour</i>
Water displacement:	<i>Excellent</i>
Protection duration in months:	<i>Indoor storage: 6 months</i>
Condensation test to DIN 50'017:	<i>1 test cycle without corrosion</i>
Consumption per m2 (dip method):	<i>Approx. 2 g</i>
Application:	<i>Dip, spray, brush</i>
Film removal:	<i>By neutral or alkaline detergent, or solvent</i>

Physical/chemical data:

Viscosity:	<i>1.3 mm²/s</i>
Specific gravity:	<i>0.80 g/cm³</i>
Flashpoint:	<i>40°C</i>
Drop point without solvent:	<i>35°C</i>

Safety and environmental aspects:

ADR/RID:	UN 1993
Precautions:	Do not allow product to get into ground water, water course or sewage system.
Water hazard class:	Slightly water endangering (WGK 1)
EC waste code:	12 01 07 / 13 08 99 / 20 01 13
CH waste code:	Identical to EC waste code (as per VeVA of 01.01.06)
Classification and labelling:	Stated in the safety data sheet



Container sizes:

Drum: 208 l

Canister: 5 l • 25 l

The data given on this sheet are based on properties and application possibilities as known to us. No general legal liability can be derived from these data. Blaser Swissslube AG will assume no liability for damage resulting from improper use of the products. 39.539 E (0721)