

Blasoprotect MV 28

Art. 128-02

Description: Blasoprotect MV 28 is a water repellent anti-corrosion fluid. Offers a dry, non-sticky film, set no dust, must not be removed in further processing.

Applications: – Relieves metallic workpieces after production of aqueous cooling lubricants and prevents the invasion of water in following washing baths. Does not allow to form condensation during storage.

Product characteristics

- Thin protection film sufficient
- Treated parts deposit no dust
- Displaces water

Benefits

- Small consumption
- Parts can be processed without subsequent treatment
- Water repellent effect, ideal for blind holes

Product-related data:

Film type:	<i>oily</i>
Film thickness by dip method:	<i>0.5 µm</i>
Drying time at room temperature:	<i>2.5 h</i>
Water repellent:	<i>preferably used</i>
Protection duration in months:	<i>indoor: 6</i>
Condensation test to DIN 50'017:	<i>1 cycle without corrosion</i>
Consumption per m ² (dipping method):	<i>approx. 2 g</i>
Application:	<i>dip, brush</i>
Film removal:	<i>by neutral detergent, alkaline cleaner, or solvent</i>

Physical-chemical data:

Density:	<i>0.80 g/cm³</i>
Flashpoint:	<i>72°C</i>

Safety and environmental aspects:

ADR/RID:	UN 3082
Precautions:	Do not allow product to get into ground water, water course or sewage system. Danger to drinking water if even at the slightest quantities leak into the ground.
Water hazard class:	Highly water endangering (WGK 3)
EC waste code:	12 01 07 / 13 08 99
CH waste code:	Identical to EC waste code (as per VeVA of 01.01.06)
Classification and labelling:	Stated in the safety data sheet



Container sizes:

Drum: 208 l

Canister: 25 l

All information given here is based on the product characteristics and applications known to us, but no legal obligation or liability can be derived in general therefrom. Blaser Swissslube AG cannot be held liable for any damages resulting from the improper use of its products.

39.540 E (0721)