

Blasoprotect OV 36

VOC-free

Art. 136-02

Description: Blasoprotect OV 36 is a thin-flowing anticorrosion fluid free of solvents and amines. Ideal for roofed-over storage of bare metal parts and machinery. Produces a thin transparent protective film.

Applications: For protecting tools and dies, jigs, fixtures and bare metal parts against corrosion, for intermediate storage of machinery, and in all cases where temporary but effective corrosion protection is required.

Product characteristics

- VOC and amine free
- Good adhesion
- Good compatibility with lubricants
- Does not attack mineral oil proof elastomers

Benefits

- better workplace hygiene.
- lasting protection, also against humidity, for longer machine and component life.
- no need to remove protective film.
- wide application range.

Product-related data: Viscosity: 5.9 mm²/s (40° C)
Density: 0.85 g/cm³ (20° C)
Flashpoint: 120° C

Physical/chemical data: Film type: oily - waxy
Film thickness by dip method (in µm): 15 (after 24 h)
Drying time at room temperature: dry after 3 hours, remains oily
Water displacement: limited suitable
Protection duration in months: dry indoor storage: 30, roofed over: 4-6
Condensation test to DIN 50017: 15 test cycles without corrosion
Consumption per m² (dip method): approx. 15 g
Application: dip, spray, brush
Film removal: by neutral detergent, alkaline cleaner, or solvent

Safety and environmental aspects: ADR/RID: Not classified as hazardous by transport regulations.
Precautions: Do not allow product to get into ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
Water hazard class: Water endangering (WGK 2)
EC waste code: 13 02 05
CH waste code: Identical to EC waste code (as per VeVA of 01.01.06)
Classification and labelling: Stated in the safety data sheet



Container sizes: Drum: 60 l • 208 l

Canister: 4 kg • 25 l

All information given here is based on the product characteristics and applications known to us, but no legal obligation or liability can be derived in general therefrom. Blaser Swissslube AG cannot be held liable for any damages resulting from the improper use of its products.

39.558 E (0721)