

# Motor oil Blasol FEO 10W40

Art. 245-50

**Description:** Blasol FEO 10W40 is a classic, fuel-efficient, semi-synthetic low-viscosity engine oil of the SAE-class 10W-40.

**Application area:** Blasol FEO 10W40 is used in gasoline and diesel engines in cars, light-duty vehicles and motorcycles. It's also suitable for high-performance engines with direct injection, turbo and multi-valve technology.

### Product characteristics

- High performance level and favourable viscosity class for all climatic conditions →
- Good cold-start behaviour. Good high-temperature resistance →

### Benefits

- Saves fuel
- High wear protection and maximum operational safety

### Specifications/ approvals:

Blasol FEO 10W40 fulfills and exceeds the international specifications in accordance with:

ACEA	A3 / B4
API	SP
JASO	MA-2

In addition Blasol FEO 10W40 complies with the following requirements:

- Mercedes Benz	MB-Approval 226.5/229.3
- PSA	B71 2300
- Renault	RN 0700/0710
- Volkswagen	501.01 / 505.00

### Technical data:

Viscosity:	10W-40	ASTM
Density at 20°C:	0.860 g/cm <sup>3</sup>	DIN 51757

### Safety and environmental aspects:

ADR/RID:	Not classified as hazardous by transport regulations.
Precautions:	Must not be allowed to get into waste water, ground water, surface water or the soil. Even slight leakage into the soil pollutes drinking water.
Water hazard classification:	Slightly water endangering (WGK 1)
LVA/EU-waste code:	13 02 05
CH-waste code:	Identical to EU waste code (as per VeVA of 01.01.06)



**Container sizes:** Drum: 60 l • 208 l    Canister: 10 kg • 5 l • 25 l    Bottle: 1 l

The engine oil specifications listed are subject to rapid change rhythm. Therefore, subject to change. The data given on this sheet are based on properties and application possibilities as known to us. Blaser Swisslube AG cannot be held liable for any damages resulting from the improper use of its products. No general legal liability can be derived from these data. 30.541 E (1025)