

Blasolube 492

Art. 00492-01

Description: Blasolube 492 is a high pressure lubricating grease with soft consistency for universal use.

Application: – Lubrication from low to medium speed roller and sleeve bearings etc.
– Construction- and agricultural machinery

Product characteristics

- Mixed soaped grease LI/CA
- Very good adhesion
- Special high pressure additives

Benefits

- very steadily on vibrations, milling- and water influences
- grease is not hydroextracted; protection from wetness etc.
- Lubrication requirements are ensured also under high pressure

Physical/ chemical data:

Application temperature range:	-20°C to +120°C	
Grease type:	Lithium/Calcium Grease	
Alloy type:	KP 2 K-20	DIN 51502
Penetration class:	NLGI 2	DIN 51818
Normal penetration (60 Hub) in 1/10 mm:	270-290	ISO 2137
Colour, appearance:	fawn	
Pour point:	185°C	ISO 2176
Oil viscosity at 40°C:	150 mm ² /s	DIN 51562.1
Oil bleeding after 7 days at 40°C:	2.5%DIN 51817	
Shell-Roller test (mechanical stability):	320	ASTM D 1831/ISO 2137
EMCOR test (corrosion protection):	0	DIN 51802
Speed characteristic d _m x n:	Up to 325 m/min.	
Media resistance:	– cold water – warm water – Alkaline solutions – Acidic solutions	

Safety and environmental aspects:

ADR/RID:	Not classified as hazardous by transport regulations
Precautions:	Do not allow product to get into ground water, water course or sewage system.
Water hazard class:	Slightly water endangering (WGK 1)
EC waste code:	12 01 12
CH waste code:	Identical to EC waste code (as per VeVA of 01.01.06)
Classification and labelling:	Stated in the safety data sheet



Container sizes:

Drum: 180/50 kg

Canister: 14 kg

Cartridge: 400 g • 400 g L-SH

All information given here is based on the product characteristics and applications known to us, but no legal obligation or liability can be derived in general therefrom. Blaser Swissslube AG cannot be held liable for any damages resulting from the improper use of its products.

31.517 E (0218)