

# DRY PTFE Spray

## Dry lubricant spray with PTFE

Art. 651

**Description:** Food-grade IFL synthetic dry lubricant spray with PTFE (Teflon) for the food, animal feed and pharmaceutical industries and their suppliers.

**Applications:** – Ideal for slideways and chutes, worktable surfaces, cutter blades, and wherever a mineral oil free non-stain lubricant film is required.

### Benefits

- Colourless; leaves no stains
- Lubricates metallic and non-metallic surfaces
- Resistant to water, chemicals and solvents
- FDA, Gr. 21 CFR 178.3570 NSF H1 Reg.

<b>Safety and environmental aspects:</b>	Propellant gas:	Propane/Butane
	ADR/SDR:	2.1/5F
	Precautionary measures required:	Water-polluting (active agent)
	EC-waste code:	16 05 04
	Manufacturer:	Rocol Ltd, Leeds (GB)

<b>Physical/chemical data:</b>	Colour:	Colourless
	Density at 20°C:	0.6 g/cm <sup>3</sup>
	Flashpoint:	< 0°C
	Maximum application temperature:	+ 250°C

<b>Suitability:</b>	Solid additives:	PTFE
	Corrosion protection:	•
	Adhesion:	••
	Penetration:	••
	Creep properties:	•
	Durability:	••
	Lubricity:	••

<b>Resistance to:</b>	Cold water:	•••
	Warm water:	••
	Hot steam:	••
	Alkaline solutions:	••
	Acidic solutions:	•••

••• excellent    •• good    • satisfactory, must be clarified



**Container sizes:** Spray: 400 ml

*These specifications are subject to rapid change. Alterations are therefore possible. The data given on this sheet are based on properties and application possibilities as known to us. No general legal liability can be derived from these data. Blaser Swisslube AG will assume no liability for damage resulting from improper use of the products.*

39.531 E (0112)