

Blasoslide CGLP

Art. 00750-01 – 00754-01

Description: The Blasoslide CGLP series are slideway oils for slideways consisting of various material combinations. They are based on modern formulas and are available in well-established viscosity grades.

- Applications:**
- Developed with a focus on the lubrication of slideway machine tools and optimised for the best possible compatibility with our Blaser cooling lubricants
 - Main application is where an extremely adhesive and compact lubricating film is required
 - Suitable for lubricating a wide range of applications in various industries
 - Designed for the lubrication of various lubricating points in the metal, wood and plastics industries

Product characteristics

- Excellent adhesion
- Broad material suitability
- Optimum lubricating capacity and uniform sliding behavior
- High demulsibility
- State-of-the-art base oil platform
- Corrosion and wear protection for broad range of metals

User benefits

- The required lubricating film remains on vertical guides and under high loads.
- Can be used for a broad range of different construction types and material combinations in a variety of applications.
- Prevents stick-slip. This ensures a reliable machining process.
- Extended service life of slideways and guides.
- Best possible compatibility with Blaser metalworking oils in order not to affect their performance and quality level and to ensure a long service life of Blaser water-miscible cooling lubricants.
- Contributes to maximum durability and highest precision of the slideways.

Physical - chemical data:

Art.	Alloy grade		Viscosity 40°C ISO-VG class (mm ² /s)	Viscosity 100°C (mm ² /s)	Viscosity- index VI	Density 20°C (g/ml)	Pourpoint (°C)	Flash point (°C)
	DIN 51502	ISO 19378	DIN 51562 ISO 3448	DIN 51564	DIN 51564 ISO 2509	DIN 51757	DIN 51579 ISO 3016	DIN 51376 ISO 2592
00750	CGLP	GA, GB	32	5.5	113	0.849	-21	220
00752	CGLP	GA, GB	68	9.2	111	0.858	-21	232
00753	CGLP	GA, GB	100	11.8	108	0.862	-18	256
00754	CGLP	GA, GB	220	19.6	101	0.882	-15	264

Appearance:	Clear, yellow	
Coppercorrosion:	1	DIN EN ISO 2160
FZG Damage force level:	>10	ISO 14635-1
Cobalt leaching:	<5ppm	


Oil change recommendation: see overleaf

Blasoslide CGLP

Art. 00750-01 – 00754-01

Oil change recommendation: Blasoslide CGLP is generally miscible and compatible with other mineral oils. To ensure the full performance of the product, use of a single type of oil is recommended.

Safety and environmental aspects:	– ADR/RID:	No dangerous goods according to the transport regulations.
	– Precautionary measure:	Do not allow product to reach ground water, water course or sewage system. Harmful to aquatic organisms.
	–Water hazard classification:	Weakly water hazardous (WGK 1)
	–EC-waste code:	13 02 05*
	–CH-waste code:	13 02 05
	–Classification and labelling:	Not classified

**Container sizes:**

Container: 1022 L

Drum: 208 L (60 L available only for CH)

Canister: 25 L • 10 L

All information given here is based on the product characteristics and applications known to us, but no legal obligation or liability can be derived in general therefrom. Blaser Swissslube AG cannot be held liable for any damages resulting from the improper use of its products.

34.546 en (0126)